




REVISIONS							
ECR	DESCRIPTION	DATE	INITIAL	APPROVED			
	RELEASED FOR PRODUCTION.	4/19/2016	RJC	JAG			
		5/16/2016	RJC	JAG			
16-0059	RBT18024 FOR LONGER BOLTS, DELETED CUT OUT FOR CONNECTOR ASSY., ADDED CUTOUT FOR RBT18033 -15, -17, -19, AND -27 DELETED. ADDED RBT1803329 CH'D SUPPLIER P/N WAS #BQ-BQ101	6/24/2016	RJC	JAG			
	ADDED CUTOUT FOR RBW109-3101-58-211 REPLACED W/ RBT18561-3135 ADDED RBW109-3101-	9/6/2016	RJC	JAG			
17-0127	3101-58-2-13 CH'D MAT'L WAS 'Y-20 BLACK IS ETHAFOAM 220, BLACK, CH'D DIMS WAS 3.29 IS 6.41, WAS 2X 7.42 IX 8.98. CORRECTED CUTOUT FOR RBTI 8522. ADDED DETAIL VIEWS 8, C, D, E ON SHEET 3, -3, -5 CH'D B/O REF WAS (I.R. SPECIALTY) IS (CASE SOLUTIONS), -5 CH'D MAT'L WAS Y-20, BLACK IS ETHAFOAM 220, BLACK,CH'D RIBBON HANDLE NOTE. ADDED DIMS ▼.86,27.81, 6.23. DELETED DIM 20°9 ADDED DRAWING TO MODIFY B/O ADDING SLOT TO END OF HANDLE23 CH'D B/O REF WAS PARAMOUNT #05 45104 IS (PARAMOUNT #0545091), -35 CH'D TOLERANCES WAS ±.005 IS ±.010, WAS ±.01 IS ±.03. CH'D ITEM 12 WAS RBW109-3101-58-1 IS RBW109-3101-58-1-1. CHD ITEM 13 WAS	5/31/2017	DPD	JAG			
	16-0051 16-0059 16-0143	ECR DESCRIPTION RELEASED FOR PRODUCTION. 16-0051 -1 CH'D QTY WAS 2 IS 1, -3 CH'D TOOL CUTOUTS FOR -21, RBT18547, RBT18552, RB PWC70403, RB PWC34941 FOR BETTER FIT. CH'D B/O INFO WAS RB PWC70403 IS RB PWC34910-200.	DATE	DESCRIPTION DATE INITIAL			





ASSY QTY	ASSY QTY	B/O	Part #	UNIT	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
				1	BORESCOPE GUIDE TUBE		RB PWC34910-200	1
				1	SEAL INSTALLATION WORKAID		RBT18026	1
				1	LUBRICATION WORKAID		RBT18028	1
				1	SIGHT GLASS PULLER		RBT18552	1
				1	FIXTURE HOLDING		RB PWC34913	1
				1	T/R GEAR BOX DRAIN TOOL		RBT18547	1
				1	M/R TAB BENDER		RB T101654-101	1
				1	PULLER, WRENCH		RB PWC34941	1
				1	SWASHPLATE LINK AND DRIVE LINK BEARINGS WORK AID		RBT18024	1
				1	HAMMER, STEEL, BLADE CORROSION AND VOIDS DETECTION		RBW109-3101-58-1-1	1
				1	HAMMER, ALUMINUM, BLADE CORROSION AND VOIDS DETECTION		RBW109-3101-58-2-1	1
				1	BEND ANGLE GAGE, TRIM TAB		RB T101656-145	1
				2	BLADE BOLT BULLET		RB T101266-101	1
				1	JACK SCREW SET		RB T101308	1
				1	ADJUSTABLE SPANNER WRENCH		RB AN8514-1	1
				1	BATTERY TEMP CAUTION LIGHT TESTER		RBT18033	5
				1	10X MAGNA-LITE		RBT18561-31	1
		B/O	-1	1	CASE	PLASTIC	PELICAN #APP-1700-E	N/
		B/O	-3	1	воттом гоам	ETHAFOAM 220, BLACK	3.00 X 13.63 X 35.63 (CASE SOLUTIONS)	2 &
		B/O	-5	1	TOP FOAM	ETHAFOAM 220, BLACK	2.06 X 13.62 X 35.62 (CASE SOLUTIONS)	4
		B/O	-7	1	STIFFENER	COROPLAST	.24 X 9.72 X 35.62 BLACK (I.R. SPECIALTY)	5
		B/O	-9	1	LG. DZUS SCREWDRIVER		(SNAP-ON #S6180)	6
		B/O	-13	1	LINEAR SCALE	BRASS	50 LB X 80Z AMERICAN SCALE #IN-050M	1
	Х		-21	1	ROTOR BRAKE MASTER CYLINDER TESTER			7
	1	B/O	-23		GAUGE	S.S	3-1/2in. 1/4L 600 psi {ASHCROFT #1009SW, PARAMOUNT #0545091}	7
	1	B/O	-25		ELBOW	BRASS	1/4 NPT 90° (MCMASTER-CARR #50785K36)	7
	1	B/O	-29		BRAKE HOSE		PACIFIC RUBBER #BQ101-HFIM19-HFIF03+5406-4-2@18" OAL	7
	1	8/0	-31		BOND SEAL WASHER		(PACIFIC RUBBER #BRE9900-4)	7
	1	B/O	-33		COUPLING HALF, HOSE ATTACHING	ALUMINUM	(EATON #375508-5)	7
			-35	1	RED LOCATION CARD	LAMINATED CARD		8
		B/O	-37	1	LANYARD	COATED STEEL	Ø1/16 X 14 {CARR LANE #CL-2-C}	N/
		B/O	-39	2	FERRULE	ALUMINUM	Ø1/16 X 3/8 (MCMASTER-CARR #3896T31)	N/
		B/O	-41	1	GROMMENT	NICKEL-PLATED BRASS	SIZE 00, Ø.42 OD (MCMASTER-CARR #86625K31)	N/
		B/O		1	DART PLACARD	ALUMINUM	RB41011	N/
	ASSY -21							













		REVISIONS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
5	17-0127	-9 ADDED DRAWING TO MODIFY B/O ADDING SLOT TO END OF HANDLE.	5/31/2017	DPD	JAG







DART

412 FIELD MAINTENANCE KIT

DWG NO. RBT18025-9 MAT'L UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

.XXX ± .005 FRACTIONS ± 1/8

.XX ± .01 ANGLES ± .5°

.X ± .1 SURFACES = 125/ SPEC A T.I.

1. BREAK ALL SHARP EDGES


.015 x 45° OR .015R

2. DIMENSIONAL LIMITS APPLY
AFTER PLATING
3. INTERPRET DIM AND TOL PER
ASME Y14.5M-2009 DRAWN BY: CLOUGH CHECKED: DUERFELDT OPPS APPR: ANDERSON QA APPR: LINDSAY USED ON MODEL APPROVED: GILBERT SCALE 1:2 3/6/2017 SHEET 6 OF 8



LG. DZUS SCREWDRIVER

REVISIONS						
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED	
3	16-0059	-21 DELETED -27 FROM ASSY, CH'D SUPPLIER P/N WAS #BQ-BQ101 IS BQ101-HFIM19-HFIF03+5406-4- 2@18" OAL.	6/24/2016	RJC	JAG	



(-21


ROTOR BRAKE MASTER CYLINDER TESTER


DART

412 FIELD MAINTENANCE KIT

DWG NO. RBT180			025-21		5	
MAT'L HEAT TREAT FINISH					S	
SPEC			1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING			
DRAWN BY: CLOUGH						
CHECKED: DUERFELDT						
OPPS APPR: ANDERSON				3. INTERPRE ASME Y14.	F DIM AND TOL PER 5M-2009	
QA APPR: LINDSAY				USED ON MODEL		
APPROVED: GILBERT			H175 4/18/2016 SHEET 7 OF			
SCALE 1:4 DATE 4/						


REVISIONS								
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED			
3	16-0059	-35 CH'D DIM WAS 10.63 IS 9.17.	6/24/2016	RJC	JAG			
4	16-0143	-35 ADDED RBW109-3101-58-2.	9/6/2016	RJC	JAG			
5		-35 CH'D TOLERANCES WAS ±.005 IS ±.010, WAS ±.01 IS ±.03, CH'D ITEM 12 WAS RBW109-3101-58-1 IS RBW109-3101-58-1-1, CH'D ITEM 13 WAS RBW109-3101-58-2 IS RBW109-3101-58-2-1. CH'D GRAPHICS TO REFLECT NEW CUTOUT FOR ITEM 5.	6/1/2017	DPD	JAG			





FRONT SIDE OF CARD BACK SIDE OF CARD

NOTE:
THE CARD PAPER IS TO BE RED AND LAMINATED.
THE CARD WILL BE ATTACHED TO A LANYARD WITH A GROMMET. THE OTHER END OF THE LANYARD CABLE WILL BE ATTACHED TO THE LEFT REAR (WHEEL END) OF THE PELICAN CASE.





RED LOCATION CARD